

LED Full Color Outdoor Video Display System



Light Emitting Diodes (LED) as a photonic semiconductor converts electric energy to light energy, to emit visible light photon. (Red/Green/Blue)

Features of Display Systems

- Modularized Design
- Supporting Standard VGA, NTSC, PAL and SECAM Video System
- Input - Composite Video, S-Video, VGA
- Real time Self-Diagnostic
- Auto brightens adjustment
- Real 60 Hz flicks free image processor
- Software for remotely controlling communication and scheduling
- Optic fiber data transmission



Optimal Viewing Distance

As a general rule, we usually recommend a pixel pitch equal to the minimum viewing distance in mm

- For an example - a screen intended to be viewed from 10m ~ 15m may use a 10mm ~12.5mm pitch.

Pitch Size	Min ~ Max
• Pitch 12.5mm	= 10 ~ 15 meter
• Pitch 16mm	= 15 ~ 75 meter
• Pitch 20mm	= 20 ~ 100 meter
• Pitch 25mm	= 20 ~ 150 meter
• Pitch 32mm	= 25 ~ 200 meter
• Pitch 35mm	= 30 ~ 250meter

Quality Assurance

The full quality assurance program covers concept design, manufacturing, fabrication and technical management database of each product in accordance with ISO 9001 to customer's complete satisfaction.



Suntec City




Liat Tower



ComCentre

16 bits Display Technology

- Perfect Gamma corrective curve
- Solarization problem solved
- CRT – like LED display
- True Color Reproduction
- Ultimate Color Accuracy
- Uniform Color
- Dynamic Contrast Enhancement
- Flicker Free Picture – Noise Reduction
- Very smooth image, especially in low brightness area environment



16 Bit


Virtual Pixel

A technology to make each LED shared by surrounding pixels to gets :-

- Higher resolution by 3 times
- Unique appearance
- The formation of the LEDs layout is different from the normal LED cluster type, because the LED shared technology.
- These technology help to reduce cost for screen with less resolution dots. But still maintain the high virtual image display. Such as 4m x 3m Screen
- It is workable for running Video or Animation image only, but not so much for detail text.




8 Bit




Features of clutters, panels & modules


- UV resistant polycarbonate shell and silicon /epoxy filled cluster panel for outdoor application
- Easily installed and waterproof module design
- High precision CNC housing design
- Automotive level coating for severe working environment
- Constant current driving technology to reduce heat generation
- 1% ~ 100% brightness levels adjustment for each R/G/B
- Built-in self test pattern for easy maintenance
- High efficient power factor design
- CE, UL, ETL approval optional
- Custom-made design acceptable



SMD Matrix Unit



LED Matrix Unit



3 in 1 SMD Matrix Unit



CBD eVision Pte Ltd

69 Ubi Crescent #02-02 CES Building Singapore 408561 Tel: 6288 8233 Fax: 6283 2828
 Email: johnny@cbd-evision.com www.cbd-evision.com



Trivision Display System

Manufactured in all possible billboard sizes, CBD eVision's leading three-message sign expands the marketability of high-traffic locations without increasing the number of billboards in the cities. It optimises the advertising site by minimising the investment in structure, illumination and location.



Bugis Junction



Thai Embassy




Mah Showroom



Eminent Plaza

Your imagination is the only limit to the shape of signs that we can make. We have already made circular, half-circular, concave, convex, elliptical, square, box-shaped signs... can you think of another form? We can probably do it too!



Causeway



NTUC



What CBD Trivision?

It is an outdoor billboard that consists of three-faced prisms which slowly rotate 120 degrees and then pause, before starting a new rotation cycle. CBD Trivision reduces the amount of billboard sites needed. The three faces increase the communication potential, which allows the investment in structure and illumination to be shared between the three messages.

In an industry where location is everything, changeable-message technology is expanding the marketability of high-traffic locations without increasing the number of billboards. Indeed, they offer a more comprehensive, yet economical and effective option. A major advantage for advertisers is the creative options available to them, but advertisers aren't the only beneficiaries. It's a win-win situation all the way around. The community gets better quality signs, and the outdoor companies see greater profit.



The environment, a global and growing issue

Nowadays, it is no longer enough to conduct business in an effective and ethical manner - you also have to show that the environment is on your priority list, that you consider the impact of your product on the environment and that you are truly committed to this issue by showing concrete solutions.

The number of billboards having increased constantly and significantly over the years, the expression "billboard pollution" has become frequently used. Nowadays, fewer and better quality sites is the upward trend. Marketing effort of the contractors have changed and the focus is now on offering more effective sites rather than a great quantity at a lower quality. There is also an increasing sophistication of billboards which translates into, for instance, more sites with illumination, double sided billboards, as well as billboards with clocks, flower beds, park benches, etc. The maintenance of sites is also greatly improving.

CBDflex on the right road

We introduced CBDflex, our variable message sign for road applications. Very quickly, this new product gained popularity to the extent of being used today in major projects. Some of the existing applications are speed limit, road deviation and parking information.



CBD eVision Pte Ltd

69 Ubi Crescent #02-02 CES Building Singapore 408561 Tel: 6288 8233 Fax: 6283 2828
Email: johnny@cbd-evision.com www.cbd-evision.com

JVC

PROFESSIONAL

42-INCH PLASMA DISPLAY MONITOR

GM-P420E

High-Resolution, Flat Plasma Monitor
Delivering Bright, High-Contrast Picture
with Wide Viewing Angle



- **Superb Video Picture Quality**
- **1500:1 Contrast Ratio**
- **Super Bright Picture 370 cd/m² (Set)**
- **16.77 Million Colours/256 Levels**
- **Wide Viewing Angle (160 Degrees)**
- **Wall/Ceiling Mountable**
- **RS-232C Interface & MAKE Remote**
- **S-VGA/XGA Compatible**
- **Various Set-Up Capabilities**
- **Cooling Fanless**

Brighter, Sharper Pictures and Enhanced Flexibility

■ Contrast Ratio — 1500:1

The GM-P420E comes with sophisticated circuitry that enhances its contrast ratio to 1500:1, making it the leader in its class.


■ Actual Brightness — 370 cd/m² (Set)

Brightness has also received a strong boost compared to conventional levels. Delivering bright pictures of 370 cd/m², the GM-P420E outperforms conventional models.

■ Fanless

Due to reduced power consumption, a cooling fan is not required, which eliminates noise.

Dimensions



Speaker System (Option)



TS-C4200SPG Slim Wall-Mounted Speaker System

Specifications

Rated input	8 W
Nominal impedance	6 ohms
Dimensions (W x H x D)	100 mm x 610 mm x 89 mm
Weight	2.1 kg (each)

Specifications

■ DISPLAY PANEL	
Screen size (W x H)	921 mm x 518.4 mm/36-3/8 inches x 20-1/2 inches (wide 42-inch diagonal)
Aspect ratio	16:9 wide (width-to-height ratio of screen) 4:3/16:9 selectable
Viewing angle	160°
Display colours	16,777,216 (RGB each of 256 levels)
Brightness	370 cd/m ² (Set)
Resolution (H x V)	640 x 480 (4:3) 853 x 480 (16:9) S-VGA: 800 x 600 (Displayed at 640 x 480) XGA: 1024 x 768 (Displayed at 640 x 480)
No. of pixels	Horizontal 853 x Vertical 480 pixels
Display modes	
Regular (4:3)	4:3 video image displayed in centre of screen
Full/Panoramic (16:9)	Displays wide horizontal expansion of 4:3 video image for full-screen display
Zoom (16:9)	Overall expansion of 4:3 video image for full-screen display (top and bottom of image are cut)
Input connectors	
Video A Composite	BNC connectors x 2, 1 V(p-p), 75 ohms negative sync., auto-termination, bridged output possible
Video B Composite YC	RCA pin x 1, 1 V(p-p), 75 ohms, negative sync. mini-DIN 4 pin x 1 Y: 1.0 V(p-p), 75 ohms, negative sync. C: 0.286 V(p-p), 75 ohms (NTSC Burst) 0.3 V(p-p), 75 ohms (PAL Burst)
Component	Y: 1.0 V(p-p), 75 ohms, negative sync., BNC x 1 PB/B-Y: 0.7 V(p-p), 75 ohms, BNC x 1 PR/R-Y: 0.7 V(p-p), 75 ohms, BNC x 1
Compatible systems	
Video A, Video B input	NTSC/NTSC 4.43/PAL/PAL60/SECAM
Component input	480i, 576i, 480p, 720p, 1080i (1035i)
RGB A	D-sub 15-pin (3-row) x 1 Video signal: 0.7 V(p-p) Sync signal: 1.0 V(p-p) – 5.0 V(p-p), high impedance
RGB B	BNC x 5 R/B: 0.7 V(p-p), 75 ohms G: 0.7 V(p-p), 75 ohms, Sync. On G: 1.0 V(p-p) HD/CS: 0.3 V – 5.0 V(p-p), high impedance VD: 1.0 V – 5.0 V(p-p), high impedance
Audio input	Video A: RCA pin x 2 (L/R) 500 mVrms Video B: RCA pin x 2 (L/R) 500 mVrms Component: RCA pin x 2 (L/R) 500 mVrms PC: Stereo mini jack terminal x 1 (L/R) 500 mVrms
Weight	32.3 kg
■ GENERAL	
Power requirement	230 V AC, 50Hz/60 Hz
Power consumption	290 W
Audio power output	Speaker out: 6 ohms to 16 ohms 3 W + 3 W (TYP at impedance 6 ohms)
Audio out terminals	Pin jack terminal x 2 (L/R) output impedance 600 ohms
Operating environment conditions	
Temperature range	0°C to +40°C (32°F to 104°F)
Humidity range	20% to 80%, non condensation

Optional Accessories



TS-C420P4W
Stand Unit (Vertical Position)
Dimensions (W x H x D):
500 mm x 607.2 mm x 700 mm



Stand Unit (Horizontal Position)
Dimensions (W x H x D):
700 mm x 384.6 mm x 452 mm




TS-C420P2W (Portrait Setting)
Wall Mounting Unit
Mounting Angle: 0°, 5°, 10°, 15°
Dimensions (W x H x D):
494 mm x 529 mm x 47 mm*



TS-C420P3W
Ceiling Suspension Unit
Mounting Angle: 0°, 10°, 20°
Dimensions (W x H x D):
570 mm x 450 mm x 165 mm*



TS-C420P7W
Stand Unit
Dimensions (W x H x D):
574 mm x 226 mm x 330 mm



TS-C420P6W
Wall Mounting Unit
Mounting Angle: 0°
Dimensions (W x H x D):
570 mm x 576 mm x 47 mm*

*At the mounting angle 0°.

TS-C01FANG
Cooling Fan Unit
Dimensions (W x H x D):
174 mm x 33 mm x 160 mm
(not including cable)

TS-C420P8W (Landscape Setting)
Wall Mounting Unit
Mounting Angle: 0°, 5°, 10°, 15°
Dimensions (W x H x D):
610 mm x 520 mm x 50 mm*

Caution: ■ PDP is an ultra modern electronic device fabricated using leading-edge technology. Therefore, its effective picture elements are 99.99 percent or more, meaning 0.01 percent or less defective elements or "always ON" portion could exist. ■ Screen burn-in: Like a CRT, PDP uses phosphor; therefore, burn-in could result from long-term use such as displaying the same still picture.

Design and specifications subject to change without notice.

JVC

DISTRIBUTED BY

VICTOR COMPANY OF JAPAN, LIMITED

SPECTRUM LED Multi-Line System

CBD eVision LED Multiline Display System is designed to improve customer or employee communications. In busy reception area, hotels, lift lobby and clubs, frequently changing information needs to be displayed to visitors. In more public areas like Airports, Bus and Railway Terminals, constantly changing passenger information has to be clearly understood.

In factories, offices and warehouses effective communication with employees is vital. Process or production control information can be clearly displayed and automatically up-dated.

CDB eVision LED Multiline Display System versatility enables users to have a system to suit their particular needs. It provides the ability to transmit vital information to an entire factory, plant or any office or industrial sites, from one central computer, by direct or modem links, which means a fast, reliable solution to any communication problem.

CBD eVision LED Multiline Display System displays are simple to use, can be instantly up-dated and require virtually no maintenance. The system can be expanded by adding additional modules to the single cable network without changing the software.

By utilising high quality light emitting diodes (LEDs) in 4 different character height size - 18mm, 30mm, 50mm, 100mm and 3 different colors - Red or Green or Amber are available. By choosing the right combination, CBD eVision LED Multiline can be tailored to suit most color and viewing distance requirements between 5 metres - 50 metres.



Shaw Organisation



Pricewaterhouse



Nanyang Fine Art



AirForce School




Shangri-La Hotel



Singapore Expo




Marina Mandarin Hotel



ITE - Yishun





Technical Specification

- Modular Design for ease maintenance and upgradeable.
- Battery backup for memory upon power failure up to 60 Days .
- Memory : 225pages
- With scheduler program
- Message mode: shift, scroll, flashing, bold, upper and lower case, etc.
- User friendly menu driven software
- Power input : 230v
- Able to transmit message to single sign or multi signs.
- Interface: Rs232 or Rs485
- Character height: 18mm, 30mm, 50mm, 100mm
- Indoor Use, Semi-Outdoor Use, Fully Outdoor Use.

Construction

The case is constructed from high grade aluminum extrusion with an aluminum back panel. The back panel has built-in LED Modules, Switching Power units, Main board, and communication ports. The standard model is design for surface wall mount only. Other design of cabinet is available with additional cost. The standard design cabinet is for surface wall mount, black color aluminum housing.

Each LED Multiline display is consists of LED module, Logic Controller, Switching Power Unit. The LED Module is a range of standard sizes as well as larger displays custom built to special order.

Completing the construction, is an anti-reflective screen, which gives a high definition to the characters. The screen is easily removed to give access for cleaning.

List of Models

Model	No of line	No of Characters	Character height
CBD-12L-30C-30mm	12	30	30mm
CBD-09L-30C-30mm	9	30	30mm
CBD-06L-30C-30mm	6	30	30mm
CBD-09L-20C-30mm	9	20	30mm
CBD-06L-20C-30mm	6	20	30mm



Suntec City



Ministry of Education




Marina Square Mall



CBD eVision Pte Ltd

69 Ubi Crescent #02-02 CES Building Singapore 408561 Tel: 6288 8233 Fax: 6283 2828
 Email: johnny@cbd-evision.com www.cbd-evision.com



LED Moving Message Information & Ticker Display

LED Moving Message

Technical Specification

- LED Character Height available: 30mm, 50mm, 100mm
- Number of Character per line: 10, 15, 25, 30, 40, 50
- Number of Line: Single or Double
- Languages available: English, Malay, Chinese, Japanese
- Indoor or Semi-Outdoor or Fully Outdoor Use
- Surface Wall Mount, Ceiling hanging or Custom design
- Wired or Wireless keypad operation
- Built-in Rs232 port
- Display mode: Speeds control, Flashing, Appear. Wipe, Roll, Jump, Shoot character (one by one) Lower & Upper case, built-in graphics, Shift
- LED Color: Single color - Red, Tri-color: Red/Yellow/Green
- Proven quality - marketed for 15 years



Capital Square

LED Indoor & Outdoor Ticker Display

Technical Specification

- LED Character Height available: 50mm, 100mm, 300mm, 500mm & special size
- LED Color: Single color - Red or Green or Amber or Tri-color
- Indoor or Outdoor Use
- Length: Custom design
- Input data: direct from PC or life-feed from Bloomberg, Reuter
- Auto brightness Sensor
- Languages: English, Malay, Simplified Chinese



Marine Parade CC



Food Court



Fashion Show



Reception Counter





CBD - LED-RED COLOR MOVING MESSAGE DISPLAY

MODEL	NO. OF LINE	NO. OF CHARACTER PER LINE	CHARACTER HEIGHT	RESOLUTION DOTS	DISPLAY AREA	CABINET DIMENSION
210BHR	1	10	50mm	7 x 60	50 x 460mm	110 x 530 x 50mm
215BHR	1	15	50mm	7 x 90	50 x 690mm	110 x 760 x 50mm
220BHR	1	20	50mm	7 x 120	50 x 920mm	110 x 1000 x 50mm
230BHR	1	30	50mm	7 x 180	50 x 1370mm	110 x 1450 x 50mm
240BHR	1	40	50mm	7 x 240	50 x 1830mm	110x 1910 x 50mm
410BHR	1	10	100mm	7 x 60	100 x 920mm	190 x 1000 x 50mm
415BHR	1	15	100mm	7 x 90	100 x 1380mm	190 x 1450 x 50mm
420BHR	1	20	100mm	7 x 120	100 x 1840mm	190 x 1900 x 50mm
2-115BHR	2	15	30mm	16 x 90	75 x 430mm	160 x 480 x 50mm
2-130BHR	2	30	30mm	16 x 180	75 x 850mm	160 x 900 x 50mm
2-215BHR	2	15	50mm	16 x 90	120 x 690mm	210 x 770 x 50mm
2-220BHR	2	20	50mm	16 x 120	120 x 910mm	210 x 1000 x 50mm
2-230BHR	2	30	50mm	16 x 180	120 x 1370mm	210 x 1450 x 50mm
2-240BHR	2	40	50mm	16 x 240	120 x 1820mm	210 x 1900 x 50mm
2-410BHR	2	10	100mm	16 x 60	240 x 920mm	320 x 1000 x 60mm
2-420BHR	2	20	100mm	16 x 120	240 x 720mm	320 x 1900 x 60mm
2-430BHR	2	30	100mm	16 x 180	240 x 2750mm	320 x 3000 x 60mm
2-440BHR	2	40	100mm	16 x 240	240 x 3660mm	320 x 4000 x 60mm

CBD - LED-TRI-COLOR MOVING MESSAGE DISPLAY

MODEL	NO. OF LINE	NO. OF CHARACTER PER LINE	CHARACTER HEIGHT	RESOLUTION DOTS	DISPLAY AREA	CABINET DIMENSION
220BHM	1	20	50mm	7 x 120	50 x 920mm	140 x 1000 x 50mm
230BHM	1	30	50mm	7 x 180	50 x 1370mm	140 x 1450 x 50mm
240BHM	1	40	50mm	7 x 240	50 x 1830mm	140 x 1910 x 50mm
2-220BHM	2	20	50mm	16 x 120	120 x 910mm	250 x 1000 x 50mm
2-230BHM	2	30	50mm	16 x 180	120 x 1370mm	250 x 1450 x 50mm
2-240BHM	2	40	50mm	16 x 240	120 x 1820mm	250 x 1900 x 50mm




CBD eVision Pte Ltd

69 Ubi Crescent #02-02 CES Building Singapore 408561 Tel: 6288 8233 Fax: 6283 2828
 Email: johnny@cbd-evision.com www.cbd-evision.com

THIS IS THE EXACT SIZE YOU NEED!

21ST CENTURY SIGNBOARD!

NEW COMMUNICATION!



MM-2-2030



MM-2-2030



MM-2020



MM-2-2010 (12x46CM) (4.75"x18")



MM-2-2020 (12x91CM) (4.75"x36")



MM-2-2030 (12x137CM) (4.75"x54")



MM-2-2040 (12x182CM) (4.75"x72")



MM-4010 (4"x36") (10x92CM)

MM-4015 (4"x54") (10x138CM)

MM-4020 (4"x72") (10x184CM)



MM-4015



MM-4020



CARRY BOX



WIRELESS REMOTE CONTROL KEYBOARD

LOADER BOX(COPIER)



KEYBOARD

- EACH MODEL CAN ADD RS232-C TO COMMUNICATE WITH COMPUTER, MODEM. CAN BE USED IN MULTI-VISION SYSTEM.
- EACH MODEL CAN ADD LOADER FUNCTION TO USE LOADER BOX(COPIER). YOU CAN SELL IN THOUSANDS WITHOUT TEACHING PEOPLE TO OPERATE.
- WIRELESS REMOTE CONTROL KEYBOARD AVAILABLE. EACH MODEL CAN ADD MEMORIAL CLOCK AND 99 PCS OF SCHEDULES.

DETAILED SPECIFICATION AND NEW ITEMS ARE ON THE FOLLOWING PAGES.

DISTRIBUTOR ON THE REVERSE PAGE

THREE DIMENSION SOLID CHARACTER 29-COLOR COMBINATION MOVING MESSAGE



MM-2020-COLOR
(100 × 14 × 5CM)



MM-2030-COLOR
(145 × 14 × 5CM)



MM-2040-COLOR
(191 × 14 × 5CM)



**GOOD DESIGN AWARD
FROM CETDC**



MM-4015-COLOR
(145 × 19 × 5CM)



MM-4020-COLOR
(190 × 19 × 5CM)



MM2-2030-COLOR

MM2-2020-COLOR
(100 × 25 × 5CM)



MM2-2030-COLOR-CH

MM2-2030-COLOR
(145 × 25 × 5CM)

MM2-2040-COLOR
(190 × 25 × 5CM)



CARRY BOX



MM2-2030-COLOR

- EACH CHARACTER HAS 29 KINDS OF COLOR COMBINATION.
- THREE-DIMENSION SOLID CHARACTER.
- WITH RS232-C TO COMMUNICATE WITH COMPUTER, MODEM. CAN BE USED IN MULTI-VISION SYSTEM.
- LOADER BOX (COPIER) AVAILABLE. YOU CAN SELL IN THOUSANDS WITHOUT TEACHING PEOPLE TO OPERATE.
- WIRELESS REMOTE CONTROL KEYBOARD AVAILABLE.
- MEMORIAL CLOCK AND 99 PCS OF TIME SCHEDULE.
- MOST POWERFUL FUNCTIONS, MORE THEN 100 KINDS OF PATTERNS.

- Farben (jeder Buchstabe hat 29 Farbkombinationsmöglichkeiten)
- Echte (dreidimensionale) Buchstaben.
- Dupliziervorrichtung erhältlich; Sie können tausende kopieren, ohne das Personal dafür zu schulen.
- Variable Größen, mehr Auswahl, mehr Absatz
- Speicher für 12,288 Buchstaben
- Drahtloses Programmiergerät erhältlich
- Sehr leistungsfähige Funktionen
- Signal-und Zeitkontrolle erhältlich
- Spezialprogramme für spezielle Branchen erhältlich
- Detaillierte Angaben auf separaten Blättern

Rotating street furniture

Is display advertising an important business for you? A business that you take 100% seriously?

That means that your advertisement needs to meet a number of strict requirements. 1. Your company and/or its products have to be able to use advertising to distinguish your product from those of your competitors. 2. The campaign must give your company the right image. 3. The message should be taken in by your target group and, preferably ... 4. Induce a positive change in their attitudes.

In short, an advertisement needs one thing above all; to bring in more money than was invested in it. And that can only happen if your advertisement is seen in the first place.

We at Postermatic are already well aware that "THE ART IS TO BE SEEN". Being seen, being noticed, standing out: that, ahead of all else, is the message.

Postermatic has a long background in developing advertising signs that meet the tough requirements for modern display advertising. Rotating street furniture of all types and sizes, with guaranteed high draw potential. Giving every advertising message what it has a right to: full attention!


In addition all Postermatic equipment can carry at least 6 messages. That means that a maximum of advertising space can be obtained from a minimum actual size.



▲ Billboard



▲ Landscape



▲ Indoor



▲ City



▲ Cars



Master/Slave Clock System

We won't let you fall behind!



2.3" H Display FS-CK4102LRM



4" H Display FS-CK4104LRM



7" H Display FS-CK4107LHM




12" H Display FS-CK4112OYM




15" H Display FS-CK4115OYM




26" H Display FS-CK4126OYM



32" H Display FS-CK4132OYM



Calendar Display



Time Display: 4" H
Date Display: 2" H




Time Display: 2.3" H
Date Display: 2" H

We can make the optimal system to meet your needs.

Features:

- * LED digital time display on a 12 or 24-hour basis
- * Accuracy: A class: within ± 30 sec/year
B class: within ± 2 min/year
- * Memory back-up:
A class: 50 hours
B class: 60 days
- * Operational Temperature Range:
 $-10^{\circ}\text{C} - 60^{\circ}\text{C}$
- * Time can be adjusted either by function buttons or by personal computer
- * No quantity limit for multiple-unit connections
- * Each clock can be a master or a slave clock when connected
- * Time checking is automatically executed every one hour between the master clock and all its slave clocks.
- * Transmission distance: 50M between each clock
- * Finish: metal housing
- * Can be expanded to incorporate second display
- * Can be with count down function if required
- * Can be synchronized by SEIKO's and NATIONAL's Master Clock



DATE: MTH

BCA

FOREIGN EXCHANGE RATE

CURRENCY	SELLING	BUYING
USA		
SINGAPORE		
HONGKONG		
WEST GERMANY		
NETHERLANDS		
SWITZERLAND		
UNITED KINGDOM		
AUSTRALIA		
FRANCE		
JAPAN		
MALAYSIA		
CANADA		

HOTEL PHOENIX

FOREIGN EXCHANGE	SELL	BUYING
USA		
HONGKONG		
WEST GERMANY		
NETHERLANDS		
SWITZERLAND		
UNITED KINGDOM		
AUSTRALIA		
FRANCE		
JAPAN		
MALAYSIA		
CANADA		

- Application for:
- Banks ■ Hotels ■ Airports
 - Jewellery Store
 - Foreign Exchange
 - Money Changer
 - Shopping Centres
 - Finance Company

ELECTRONIC COMPUTERISED FOREIGN EXCHANGE RATES DISPLAY



COMPUTER
INTERFACE
(optional)



INFRARED REMOTE
CONTROL KEYBOARD
(inclusive)



MODEM (Optional)

